


#40 SERIES / X-FRAME ALUMINUM PROFILE SYSTEM


XA-4040T



Material: A6063-T5 / Clear Anodize
Mass: 1.31 kg./m.

4-6 M. MAX. LENGTH


XA-4040GT



Material: A6063-T5 / Clear Anodize
Mass: 1.83 kg./m.

4-6 M. MAX. LENGTH


XA-4040H



Material: A6063-T5 / Clear Anodize
Mass: 1.62 kg./m.

6 M. MAX. LENGTH


XA-4040R



Material: A6063-T5 / Clear Anodize
Mass: 1.55 kg./m.

4 M. MAX. LENGTH


XA-4080T



Material: A6063-T5 / Clear Anodize
Mass: 2.25 kg./m.

4-6 M. MAX. LENGTH


XA-4080HD



Material: A6063-T5 / Clear Anodize
Mass: 2.81 kg./m.

4-6 M. MAX. LENGTH


XA-4080H



Material: A6063-T5 / Clear Anodize
Mass: 2.75 kg./m.

6 M. MAX. LENGTH


XA-40120TM



Material: A6063-T5 / Clear Anodize
Mass: 4.10 kg./m.

4-6 M. MAX. LENGTH


XA-4040CT



Material: A6063-T5 / Clear Anodize
Mass: 1.53 kg./m.

4 M. MAX. LENGTH


XA-4040CH



Material: A6063-T5 / Clear Anodize
Mass: 1.57 kg./m.

4 M. MAX. LENGTH


XA-4040CL



Material: A6063-T5 / Clear Anodize
Mass: 1.49 kg./m.

4 M. MAX. LENGTH

XA-4040CU




Material: A6063-T5 / Clear Anodize
Mass: 1.57 kg./m.

4 M. MAX. LENGTH

#40 / **BRACKETS**
SERIES / **ดากยึดเข้ามุม**


X-FRAME

DCM-40




Mat'l: ADC12
Allowable Load: 205 kgf.
Applicable Parts:

M8 x 20 2 PCS.




DCSM-4045




Mat'l: ADC12
Allowable Load: 205 kgf.
Applicable Parts:

M8 x 20 2 PCS.




HB-40




Mat'l: A6063-T5 / Clear Anodize
Allowable Load: 205 kgf.
Applicable Parts:

M8 x 20 2 PCS.




HB-4H-40




Mat'l: A6063-T5 / Clear Anodize
Allowable Load: 308 kgf.
Applicable Parts:

M8 x 20 4 PCS.




DCM-4H-40




Mat'l: ADC12
Allowable Load: 308 kgf.
Applicable Parts:

M8 x 20 4 PCS.




LB-40




Mat'l: A6063-T5 / Clear Anodize
Allowable Load: 167 kgf.
Applicable Parts:

M8 x 16 2 PCS.




DC-40




Mat'l: ADC12
Allowable Load: 215 kgf.
Applicable Parts:

M8 x 20 2 PCS.




SS-40




Mat'l: SS-400 / Bright Chrome
Allowable Load: 180 kgf.
Applicable Parts:

M8 x 16 4 PCS.




HB-4080




Mat'l: A6063-T5 / Clear Anodize
Allowable Load: 308 kgf.
Applicable Parts:

M8 x 20 4 PCS.




LB-4080




Mat'l: A6063-T5 / Clear Anodize
Allowable Load: 235 kgf.
Applicable Parts:

M8 x 16 4 PCS.




DC-4080




Mat'l: ADC12
Allowable Load: 308 kgf.
Applicable Parts:

M8 x 20 4 PCS.



HB-8H-4080




Mat'l: A6063-T5 / Clear Anodize
Allowable Load: 441 kgf.
Applicable Parts:

M8 x 20 8 PCS.



HB-40120



Mat'l: A6063-T5 / Clear Anodize
Allowable Load: 530 kgf.
Applicable Parts:

M8 x 25 6 PCS.

